

# DASCOM



## DASCOM DC-7600 600 DPI Color ReTransfer Smart Card Printer

### DC-7600 Features



Industrial & Commercial Grade Design



Over The Edge Full Card Printing



High Definition Printing




Large Card Feeder Capacity



Rapid Output / High Productivity



Supports Variety of Smart Card Encoders



ReTransfer print technology is the next level up to [Direct-To-Card](#) print technology. First, the image is printed on a film, then transferred from the film to the card. This technique is suitable for [Over the Edge](#), [Heavy Duty Printing](#), improves [reliability](#) and is suitable for a vast variety of card types, such as:

- TRAVEL ID CARDS
- DRIVER'S LICENSE
- ENTRY PERMIT CARDS
- STUDENT ID CARDS
- RESIDENT CARDS
- FINANCIAL INSTITUTION CARDS
- IDENTITY CARDS
- HIGH QUALITY CARD APPLICATIONS



User Friendly LCD &amp; Keypad

Large rotate button, easy maintenance

High Capacity consumables, easy replacement

AutoCard Feeder, reduces intervention

CardFeeder LOCK, prevents card tampering

Manual Card Feed Option

Rejected Card Exit, promotes quality control

Durable alloy construction, solid industrial usage

## Printer Specifications

|                              |  |
|------------------------------|--|
| <b>Print Method</b>          | Color dye sublimation retransfer technology                        |
| <b>Resolution</b>            | 600 DPI  |
| <b>Print Capability</b>      | Single Side, Double Side, Over-the-Edge, photo quality image color |
| <b>Print Speed</b>           | Single Side: 25 secs; Double Side: 55 secs                         |
| <b>Card Thickness</b>        | 20 - 50 mil thickness; 10 - 50 mil through Manual Slot             |
| <b>Security Features</b>     | Own technology DASCOCM SOC, RFID ribbon, card feeder lock          |
| <b>User Friendliness</b>     | Easy to replace consumables  |
| <b>Card Loading</b>          | Auto card feeder   |
| <b>Operating Environment</b> | Temperature: 15 - 30 °C; Humidity: 35 - 95%                        |
| <b>Storage Environment</b>   | Temperature: 5 - 45 °C; Humidity: 35 - 96%                         |
| <b>Dimensions</b>            | 12.25" (L) x 13.25" (W) x 17" (H)                                  |
| <b>Weight</b>                | 48 lbs.  |
| <b>Warranty</b>              | 3 year Warranty , Lifetime for Print Head                          |
| <b>Driver</b>                | Windows 32 and 64 bits, Windows 7, 8, 10                           |
| <b>Power Supply</b>          | Auto wide ranging 100-240V, 50/60 Hz                               |
| <b>Card Capacity</b>         | Auto Feeder: 250 cards (30 mil thickness); Manual Feed             |
| <b>Cards Supported</b>       | PVC, ABS, PET, PET-G, PC; 85.6 x 53.98 mm (ISO ID-1/CR-80 size)    |
| <b>Interface</b>             | USB 2.0, Ethernet 10/100 Duplex mode                               |
| <b>Certifications</b>        | CCC  |



A DC-7600 example of Designing and Printing ID cards using proprietary DASCOCM CardEditor software and certified consumables. DASCOCM support is available in more than 100 countries worldwide.

## DASCOCM

<http://www.dascomamericas.com>  
 Service Hotline: 540-904-0392  
 Address: 34 Lakeview Court  
 Verona, Virginia 24482  
 (877) 434-1377

## Printer Options & Consumables

|                     |   |
|---------------------|---|
| <b>Options</b>      | RFID R/W, MSR R/W, SAM R/W  |
| <b>Consumables</b>  | YMCK (500 images) , YMCKK (400 images)<br>Retransfer film (500 images) with cleaning roller |
| <b>Cleaning Set</b> | Cleaning Card, Cleaning Roller and Cleaning Swabs   |