

SMALL SIZE BIG TECHNOLOGY

C3320 / C3330

Canon imageRUNNER ADVANCE



Compact and powerful with features and functionality completely new to the Canon range.

The C3320 and C3330 A3 Colour devices are the most compact in the A3 imageRUNNER ADVANCE lineup, with the same advanced workflow and finishing options you come to expect with a Canon product. These clever, versatile devices are suitable for a broad range of customers, from SMBs to large enterprises.

Performance

Superior V2 Colour, superb print quality and new ECO Stapling and Staple On Demand capabilities. When consumables need replacing, video tutorials guide users with Video Support on User Interface (UI).



Integration

Seamlessly integrate with key software solutions from the Canon portfolio and link to other imageRUNNER ADVANCE devices on the same network.



Sustainability

C3320 and C3330 incorporate recycled material and bioplastics, Energy Star qualified, front runner TEC rating. Lower your energy consumption with 1W sleep mode.



Cost Control

Monitor, track and analyse printer activities directly from a desktop computer or the cloud and apply policies to restrict usage if needed.



Security

Multi-layered security solutions safeguard information and support compliance. HDD Data Erase protects user data and the Trusted Platform Module (TPM) function protects sensitive data such as passwords.



At a glance

- A3 multi-function device with a small footprint and greater uptime
- Copy and print in B/W and V2 Colour at 30ppm
- Staple, booklet, ECO Staple and Staple On Demand finishing capabilities



- 7" (17.8cm) full-colour WVAG LCD display touch screen
- Document Scan Lock function prevents unauthorised copy
- Full MEAP capabilities to increase workflows and increase productivity
- Improved visibility and Reminder LED to reduce forgotten originals

Canon

*achieve more.
beyond technology.*

imageRUNNER ADVANCE C3320 / C3330



Basic Specifications

| | |
|--|---|
| Operation Panel | 7" Colour WVGA LCD display |
| Memory | Standard 2GB Hard Disk Drive 250GB |
| Network Interface Connection | Ethernet 10Base-T/100Base-TX/1000Base-T |
| Other Interface (Standard) | USB 2.0 (Host) x 3, USB 2.0 (Device) x 1 |
| Copy/Print Speed | C3330: Up to 30ppm C3320: Up to 20ppm |
| First-Copy-Out Time | C3330/C3320: 8.2sec Colour / 5.9sec B&W |
| Paper Sources | Standard: 1,200 sheets Optional: Additional 2 x 550 sheet cassettes (Cassette Feeding Unit) Maximum: 2,300 sheets |
| Output Paper Capacity | 250 sheets (80gsm) |
| Finishing Capabilities | Standard: Group, Collate Optional Staple Finisher: Group, Collate, Staple |
| Warm-up Time | From Power On: 34 seconds or less From Sleep Mode: 10 seconds or less Quick Startup Mode: 10 seconds or less |
| Power Requirements | 220-240V, 50/60Hz, 4.0A |
| Power Consumption | Maximum: 1.5kw Sleep Mode: 1W or less ¹ Energy Star Qualified: Yes |
| Dimensions (W x D x H) | Main Unit: 565mm x 693mm x 878mm |
| Installation Space (W x D) | Main Unit: 1,957mm x 1,717mm Main Unit with External Finisher: 2,607mm x 1,717mm |
| Weight | Approx. 63.2kg (without toner) |
| Toner (Estimated Yield at 5% Coverage) | Colour: 19,000 Black: 36,000 |
| Cassette/s | Thin paper, Plain paper, Recycled paper, Colour paper |

Print Specifications (Standard)

| | |
|---------------------------|---|
| Printing Resolution | 1200 x 1200dpi |
| PDL Support | Standard: UFR II Optional: PS & PCL |
| Acceptable Paper Type | Heavy paper, Pre-punched paper, Envelopes ² , Pre-punched paper, Transparency, Labels, Envelopes (No.10 (COM10), Monarch, ISO-C5, DL), Tracing Paper, Bond |
| Acceptable Paper Sizes | Cassette 1: A4, B5, A5R, LTR, STMTR, EXEC, Custom size (139.7 x 182 mm to 297 x 215.9 mm), and Envelopes (ISO-C5) Cassette 2,3 and 4: A3, B4, A4, A4R, B5, B5R, A5R, 12" x 18", 11" x 17", LGL, LTR, LTRR, STMTR, EXEC, FOLIO, A-LTR, A-LTRR, ILGL, AFLS, FLS, Custom size (139.7 x 182 mm to 304.8 x 457.2 mm), and Envelopes (Monarch, COM10 No.10, DL) Manual Feed: A3, B4, A4, A4R, B5, B5R, A5, A5R, 12" x 18", 11" x 17", LGL, LTR, LTRR, STMTR, EXEC, FOLIO, A-LTR, A-LTRR, ILGL, AFLS, FLS, Custom size (98.4 x 139.7 mm to 320 x 457.2 mm), and Envelopes |
| Acceptable Paper Weights | Cassette/s: 52 to 220gsm Bypass: 52 to 256gsm Duplex: 220gsm |
| Print Driver Supported OS | PCL: Windows XP Professional/Windows Vista/Windows 7/Windows 8/Windows 8.1/Windows 2003 Server/Windows 2008 Server/Windows 2012 Server PS: Windows XP Professional/Windows Vista/Windows 7/Windows 8/Windows 8.1/Windows 2003 Server/Windows 2008 Server/Windows 2012 Server/Mac OS x 10.5 to 10.9/Mac OS x 10.6 to 10.10 URFIL: Windows XP Professional/Windows Vista/Windows 7/Windows 8/Windows 8.1/Windows 2003 Server/Windows 2008 Server/Windows 2012 Server/Mac OS x 10.5 to 10.9/Mac OS x 10.6 to 10.10 XPS: Windows 7/Windows 8/Windows 8.1/Windows 2008 Server/Windows 2012 Server |
| Direct Print | Supported Media: USB memory key, Remote UI and Web Access ³ Supported file types: JPEG, TIFF, PDF, XPS ⁴ |

All specifications subject to change without notice.

¹ 1 watt sleep mode may not be possible in all circumstances. Certain network configurations and options may prevent the device from entering deep sleep.

² Envelope support via standard cassette, 2 only.

³ XPS print from websites is not supported.

⁴ XPS requires DIRECT PRINT KIT (for PDF/XPS)-H1.

⁵ Based on ITU-T Standard Chart No. 1 mode. Please refer to the user guide for more information.

All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.



Scan Specifications

| | |
|-----------------------------|--|
| Scan Type | Duplexing Automatic Document Feeder |
| Acceptable Originals | Sheet, book, three dimensional objects (up to 2kg) Paper Weight: Single-sided scanning: 42 to 128gsm Double-sided scanning: 50 to 128gsm |
| Scan Resolution (dpi) | Up to 600 x 600dpi |
| Scanning Speed (A4, 300dpi) | Single-sided 55ipm, double-sided 27.5ipm |
| Scan Methods | Push Scan: Colour Universal Send functionality is standard. Integration with a range of optional MEAP based capture software adds powerful workflow and conversion capabilities. Please contact your sales representative for further information. Pull Scan: Colour Network Scan Gear. Scanning is instigated from a remote Windows Scan to USB Memory Key: Available on all models Scan to mobiles, internet-connected devices and cloud-based services: A range of solutions is available to provide scanning to mobile devices, internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information. |
| Paper Capacity (80gsm, A4) | 100 sheets |

Colour Send Specifications

| | |
|--------------------------|---|
| Destinations | E-Mail/Internet FAX (SMTP), Fax (option for C3320/C3330 PC (SMB, FTP, WebDAV) |
| Address Book/Speed Dials | LDAP (Max. 2000 searchable), Local (Max. 1800 including 200 Speed dials) |
| File Formats | Standard: TIFF, JPEG, PDF, PDF (Compact), PDF/A1-b Optional: PPTX+, DOCX+, PDF (OCR)+, PDF (Compac+OCR)+, PDF (Reader Extensions)+ |

Security Specifications

| | |
|----------|---|
| Standard | IP/Mac Address Filtering, IPsec, SNMP V3.0, IEEE 802.1X, Trusted Platform Module (TPM), Secure Print, Hard Disk Drive Password Lock, Data Erase, Universal Login Manager, Department ID, SSO-H, MailboxLite, Access Management System, Adobe Right Management compatibility |
| Optional | Encrypted Secure Print, Universal Send Security Feature, iR-ADV Security Kit, Removable HDD Kit, Document Scan & Lock Tracking, Encrypted PDF, HDD Encryption, User and Device signatures, Secure Watermarks, MailboxLite. |

Fax Specifications (Optional)

| | |
|----------------------------|------------------------------|
| Requires | Canon Super G3 FAX Board-AR1 |
| Number of Connection Lines | 1 |

External Staple Finisher (Optional)

| | |
|------------------------|--|
| Number of Trays | 2 |
| Loading Capacity | 600 sheets non-stapled, 50 sheets stapled |
| Paper Weight | 52 to 256gsm |
| Staple Position | Corner Stapling (All 4 corners), Double Stapling |
| Stapling Capacity | Up to 50 sheets |
| Dimensions (W x D x H) | 662mm x 646mm x 971mm |
| Weight | Approx. 40.5kg |

Inner Finisher (Optional)

| | |
|------------------------|---|
| Number of Trays | 2 |
| Loading Capacity | Standard 600 |
| Paper Weight | 52 to 256gsm |
| Staple Position | Corner, Double |
| Stapling Capacity | Standard: 50 sheets On Demand: 40 sheets ECO Stapling: binds up to 5 sheets |
| Dimensions (W x D x H) | 604mm x 525mm x 188mm |
| Weight | 7.2kg |

Booklet Finisher (Optional)

| | |
|------------------------|---|
| Number of Trays | 2 |
| Loading Capacity | Upper Tray: 1,000 sheets + Lower Tray: 1,000 sheets |
| Paper Weight | 52 to 256gsm |
| Staple Position | Corner, Double, Booklet |
| Stapling Capacity | 50 |
| Dimensions (W x D x H) | 771mm x 657mm x 971mm |
| Weight | 67.5kg |

Other Optional Accessories

Canon PCL International Font Set-A1, Canon Direct Print Kit (for PDF)-H1, Canon Direct Print Kit (for XPS)-H1, Canon Barcode Printing Kit-D1, Canon Universal Send Advanced Feature Set-D1, Canon Universal Send Security Feature Set-D1, Canon Universal Send Digital User Signature Kit-C1, Canon Secure Watermark-B1, Canon Document Scan Lock Kit-B1, Canon Remote Fax Kit-A1, Canon ADF Access Handle-A1, Canon HDD Data Encryption Kit-C9, Canon Encrypted Printing Software-D1, Access Management Kit-B1, Canon Web Access Software-H1, Canon IC Card Reader Box-A1, Canon Serial Interface Kit-K2, Canon Copy Control Interface Kit-A1, Canon Mainbody Heater-A1, Canon Reader Heater-C1

c-nassar.com/products
Follow us on Facebook & Insta @CNASSARSONS
+961-1-874363/4 sales@c-nassar.com
3729-v1-7/15



achieve more.
beyond technology.