

# ZY307Q Thermal Receipt Printer



## DESCRIPTION

### Printing

Print Method	Direct Thermal
Print Speed	200mm/s,230mm/s,260mm/s
Resolution	576dots/line or 572dots/line
Printing Width	72mm
Paper separator(option)	48mm/52mm/56mm/64mm/68mm/76mm/80mm
Interface	USB/USB+LAN/RS232C+USB+Lan/ RS232C+USB+Lan+Bluetooth/RS232C+USB+Lan+WiFi

### Memory

Input buffer	256kbytes
NV Flash	256kbytes

### Fonts

Font A	12x24
Font B	9x17
Chinese	GB18030,BIG5 24x24dots
Japanese/Korea	Optional
User-defined	Support

### Barcode

1D	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODE39/ITF/ CODABAR/CODE93/CODE128
2D	QR Code

### Detection

Sensors	Paper out, cover open, cutter jam,paper jam and black mark detection(Optional)
---------	--

### Power Supply

Input	AC 100V-240V 50/60HZ
Output	DC 24V/2.5A

### Paper

Paper Type	Thermal Receipt Paper
Paper Width	48mm/52mm/56mm/64mm/68mm/76mm/80mm
Paper Thickness	0.06~0.08mm
Roll Dia	Max. Ø 83 mm
Paper Load	Easy paper loading
Paper Cut	Manual tear or Auto-cutter

### Physical Charateristics

Working Condition	0°C~45°C, 10%~80%RH		
Storage Condition	-10°C~60°C,10%~90%RH		
Dimensions	191(D)x146(W)x129(H)mm		
Net weight	1.94kg	Gross weight	2.14kg

### Reliability

Printing head	150KM
Cutter	1.5million

### Accessories

data cable,power adaptor,power code,paper roller,CD,manual, paper separator(option)

### Packing

Individual box	Dimension 29X17X17cm(LXWXH)	1unit/carton
Master carton	Dimension 62X36X52cm(LXWXH)	12units/carton

### OS

Emulation	ESC/POS
-----------	---------

Driver

Windows XP /Vista/ Win7/Win8 /Win10/Win 2000/Win CE/  
OPOS/JPOS

SDK

Android, IOS